Flat Cable Core **GSSC Series**




Noise suppression for ribbon cables



Dimensions


						Unit:mm
Part Number	Α	В	С	D	Е	Impedance Ω/ 100MHz (1 turn)
GSSC-33.5-8	33.5	1.4	6.5	8.0	28.4	≥30
GSSC-33.5-10	33.5	1.4	6.5	10.0	28.4	≥30
GSSC-33.5-10-2	33.5	2.2	7.4	10.0	27.0	≥30
GSSC-33.5-12	33.5	1.4	6.5	12.0	28.4	≥35
GSSC-33.5-20	33.5	1.3	6.5	20.0	27.8	≥50
GSSC-40-12	40.0	1.3	6.5	12.0	35.0	≥35
GSSC-45-8	45.2	1.3	6.5	8.0	40.0	≥30
GSSC-45-12	45.2	1.3	6.5	12.0	40.0	≥35
GSSC-50-12	50.0	1.4	6.5	12.0	44.9	≥35
GSSC-58-12	57.6	1.3	6.5	12.0	52.0	≥35


Material: Soft Ferrite Operating temperature: -40 ~ 85°C








Impedance vs Frequency


























KGSAmerica KITAGAWA INDUSTRIES America, Inc.

Please request for detailed product specification data prior to purchase

Tel:1-855-EMC-PART (1-855-362-7278) Email: sales@kgs-ind.com

All statements, specifications, properties, technical information, and recommendations herein are based on tests; however, the accuracy and completeness are not guaranteed and are subject to change without notice due to product improvement and specification change. This statement is made in lieu of all warranties, expressed or implied, including the implied warranties of marketability, and fitness for purpose. KITAGAWA INDUSTRIES America, Inc. obligation under this warranty shall be limited to replacement of product that proves to be defective. Prior to use, the user shall determine the suitability of the product for its intended use, and the user assumes all risk and liability whatsoever in connection therewith. KITAGAWA INDUSTRIES America, Inc. shall have no liability for any injury, loss, or damage arising out of the use of or the inability of the inability