


Flexible Ferrite Sheet FFS Series

NEW

HF
Halogen Free



EMI Flexible Noise Suppression Ferrite Tiles





- Thin Ferrite Sheet with higher loss and more flexibility
- Higher insertion for low-frequency band and achieves excellent performance in suppressing noise

Dimensions

Unit:mm

Part Number	A	B	C	D
FFS-0.3-1010T	10	10	11.5	11.5
FFS-0.3-1020T	10	20	11.5	21.5
FFS-0.3-1515T	15	15	16.5	16.5
FFS-0.3-2020T	20	20	21.5	21.5
FFS-0.3-2030T	20	30	21.5	31.5
FFS-0.3-2525T	25	25	26.5	26.5
FFS-0.3-3030T	30	30	31.5	31.5
FFS-0.3-5050T	50	50	55	55


*custom designs available
Operating temp(°C): -40 ~ 105



- ① PET with an adhesive layer
- ② Ferrite sheet
- ③ Double-sided adhesive tape


A,B : Soft ferrite
C,D : Profile (PET with adhesive layer)

Properties




Application

EMC Suppression for IC



Mounting FFS onto IC device



Gently bend the liner while take the ferrite sheet off.



It is not advisable to reuse the product once it is removed.



KGS **KGS America**
KITAGAWA INDUSTRIES America, Inc.

Tel: 1-855-EMC-PART (1-855-362-7278) Email: sales@kgs-ind.com

All statements, specifications, properties, technical information, and recommendations herein are based on tests; however, the accuracy and completeness are not guaranteed and are subject to change without notice due to product improvement and specification change. This statement is made in lieu of all warranties, expressed or implied, including the implied warranties of marketability, and fitness for purpose. KITAGAWA INDUSTRIES America, Inc. obligation under this warranty shall be limited to replacement of product that proves to be defective. Prior to use, the user shall determine the suitability of the product for its intended use, and the user assumes all risk and liability whatsoever in connection therewith. KITAGAWA INDUSTRIES America, Inc. shall have no liability for any injury, loss, or damage arising out of the use of or the inability to use the products. No statement or recommendation contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer.

Please request for detailed product specification data prior to purchase

Volume resistivity stated on our EMI absorber flyer is meant for noise control parameters, where the absorber is considered a conductor, but not for insulation performance. Care should be taken when using absorbers. KITAGAWA INDUSTRIES America, Inc. makes no guarantees as to electrical resistivity values and accepts no liability due to short circuits where EMI absorbers are used directly on a PC Board or areas near high voltage such as for power. The products are designed for EMI noise reduction for electronics. This is not recommended for applications involving human life or extremely high accuracy. Prior to using the products in production, please verify their performance or adhesive strength of PSA for long term use. Avoid applying any external stress such as bending or high amounts of tension. Note when the absorber products are cut, bent, or pulled, there may be a possibility of creating cracks. For storage, keep products in a cool, dry, well-ventilated area at room temperature and avoid high temperatures, humidity, and direct sunlight.

Please contact the sales department at KITAGAWA INDUSTRIES America, Inc. for the use of our products prior to selecting the parts for your application.